

Terex CTT 231

12 ton fast tornkran

Maxlyft: 12 ton

Kranarm längd: 30 m 70 m

Max lyfthöjd: 62 m

Stödben



Längd: 6,0 m injektering 2,3 m

Bredd: 6,0 m



Lyftkapacitet

Terex CTT 231

			m	20	25	30	35	40	45	50	55	60	65	70
6t		30,49	t	6,00	6,00	6,00	5,10	4,34	3,76	3,29	2,91	2,59	2,33	2,10
12t		16,29	t	9,45	7,26	5,82	4,80	4,04	3,46	2,99	2,61	2,29	2,03	1,80
6t		34,82	t	6,00	6,00	6,00	5,96	5,10	4,43	3,90	3,46	3,10	2,80	
12t		18,66	t	11,09	8,56	6,91	5,74	4,87	4,19	3,66	3,22	2,86	2,55	
6t		37,31	t	6,00	6,00	6,00	6,00	5,53	4,82	4,25	3,79	3,40		
12t		19,84	t	11,89	9,21	7,45	6,21	5,28	4,57	4,00	3,54	3,15		
6t		39,76	t	6,00	6,00	6,00	6,00	5,96	5,20	4,59	4,10			
12t		21,01	t	12,00	9,85	7,99	6,68	5,70	4,94	4,34	3,85			
6t		42,33	t	6,00	6,00	6,00	6,00	6,00	5,59	4,95				
12t		22,27	t	12,00	10,53	8,56	7,17	6,14	5,34	4,70				
6t		44,43	t	6,00	6,00	6,00	6,00	6,00	5,90					
12t		23,08	t	12,00	10,97	8,94	7,50	6,43	5,60					
6t		40,00	t	6,00	6,00	6,00	6,00	6,00						
12t		24,51	t	12,00	11,74	9,57	8,04	6,90						
6t		35,00	t	6,00	6,00	6,00	6,00							
12t		26,00	t	12,00	12,00	10,23	8,60							
6t		30,00	t	6,00	6,00	6,00								
12t		26,61	t	12,00	12,00	10,50								

Radiostyrd

Elanslutning: 380 V/125 Amp

